

OR-2008A TX (EpsonI3200-A1x8)

高速数码印花机 High Speed Digital Sublimation Printer



(重型墙板-支持1000-1500米介质收放)

Heavy duty wall panel – supports feeding up to 1000-1500 meters



打印头配置技术特点 High-speed micro-piezoelectric inkjet printing technology



OR-2008ATX配置8个爱普生I3200-A1打印喷头,采用微压电喷墨打印技术,可变墨滴打印,高精度输出,工业级别设计保障打印头经久耐用。

- 智能工作效率高 Intelligent work efficiency
- 精度高速度快结构稳定 High accuracy, fast speed, stable structure
- 服务售后无忧 Worry-free after-sales service

重型墙板, 高强度的生产结构, 稳定可靠, 配备大功率电机, 气涨轴后放后收可支持1000-1500米收放, 实现无人值守的自动化生产模式, 生产力得到进一步的提升。

Heavy-duty wallboard, with a high-strength production structure, is stable and reliable. Equipped with a high-power motor, the air-expansion shaft allows for a 1000-1500 meter range of extension and retraction, enabling an unattended automated production mode and further enhancing productivity.

CMYK	CMYK * 8	CMYK * 6
I3200-A1 * 6	1pass(360x1200dpi) 320 m/h 2pass(360x2400dpi) 180 m/h	1pass(360x1200dpi) 270 m/h 2pass(360x2400dpi) 135 m/h

- 独特外观设计, 科技感十足, 美观时尚, 便捷直观的操作界面;
Unique appearance design, full of technological sense, beautiful and fashionable, convenient and intuitive operating interface;
- 智能化设计, 配置汉森北斗锐印软件;
Intelligent design, equipped with Riin software;
- 稳定连供系统, 配5L大墨瓶, 恒压稳定输出品质高;
Stable continuous supply system, equipped with 5L large ink bottles, constant pressure stable output with high quality;
- 三段可控烘干, 区域打印, 即打即干, 节约能耗;
Three stage adjustable drying, area printing, instant drying, saving energy consumption;
- 千兆网端口传输速度快, 断电续打;
Gigabit Ethernet ports have fast transmission speed and can continue to operate even when powered off;
- 可变墨滴技术, 画面层次细腻丰富。
Variable ink droplet technology, with delicate and rich layers in the image.


技术参数 Technical Characteristics




大功率电机
气涨轴后放后收装置
high-power motor
Rear loading and take-up to facilitate workflow.




5L墨桶+220ml连供墨盒
Stable bulk system ensures amazing printing speed.




三段式独立可调节压轮
New pinch roller structure of three in group brings more stable feeding precision



可支持1000-1500M介质负载
Junbo media roll maximum 1000-1500m media load.



高品质静音双导轨
High quality silent dual rail



前段走料辊装置:有效控制材料的稳定性
Front expander ensure quick and accurate take-up in high speed printing.



前端+底部红外烘干系统
Front end+bottom infrared drying system



小车增加底板加热, 有效提高打印的稳定性
Carriage bottom plate increases double-sided heating.



广泛应用:服装、家装面料、帆布袋、靠垫、踏板车、旗帜、纺织布料等。

Both the sublimation and direct-to-textile printers are examples of our expertise and engineering: top performant, reliable and precise. With GT series printer, you can maximize production while controlling quality and minimizing costs for beautiful soft signage, apparel and interior decor items that will set your business apart from the competition. Wide applications in clothing, home decoration fabrics, sampling, shirt, canvas bags, bolster, scooter, flags, textile gadgets etc.

技术参数		TECHNICAL PARAMETERS
型号 Model		OR-2008A TX
喷头 Print Head		8 * I3200-A1
颜色 Colors		YMKC
速度 Printing Speed		1pass : 320 sqm/h 2pass : 180 sqm/h
打印技术 Printing Technology		压电式喷墨打印 Piezoelectric Inkjet
介质尺寸 Ink Cartridges	宽幅 Type	1950 mm
	厚度 thickness	1 mm
	重量 Weight	200 kg (气胀轴后放后收系统, 支持1000-1500米打印 The air expansion shaft rear release and rear collection system supports 1000-1500 meters printing.)
打印宽幅 Printing Width		1950 mm
墨盒 Ink	种类 Kind	热升华墨水 Dye Sublimation Ink
	容量 Capacity	4*4 CISS (220ml 连供墨盒+报警墨瓶(5L) 220ml ink cartridge with 5L ink tank)
打印分辨率 Printing Resolution		2400 dpi
接口 Interface		千兆网口 LAN
电压 Power		AC 220V $\pm$ 10%, 50/60 HZ, 12000W
软件 RIP		锐印纺织版 Riprint
机器尺寸 / 重量 MachineSize / Weight		3935 x 1160 x 1870 mm / 550 kg
包装尺寸 / 重量 Package Size / Weight		3550 x 760 x 1760 mm / 725 kg (40GP hold 9 units)
环境 Environment	开机 Power on	温度 Temperature:15℃ to 32℃ / 湿度 Humidity: 35 to 80% (无冷凝 no condensation)
	关机 Power off	温度 Temperature:5℃ to 40℃ / 湿度 Humidity: 20 to 80% (无冷凝 no condensation)
附件 Standard Components		支架、收放料器、红外烘干系统、冷风风干系统、大供墨系统、墨囊压片等 USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.

南京欧瑞卡数码科技有限公司 Nanjing ORIC Digital Technology Co., Ltd.

地址：江苏省南京市高淳经济开发区秀山路79号

Add: No.79 Xiushan Road, Gaochun Economic Development Zone, Nanjing City, Jiangsu

网站Web：www.oric-systems.com / www.oric-systems.cn

