

OR-5806E UV (Epsoni3200x6)

3D texture gold tracing tape printer





Texture effect: 5 sqm/h,free switching between matte oil and hot golden oil



The second floor









Texture relief painting hot stamping process is applied to the three-dimensional texture effect of the image

to enhance the decorative effect and texture. The texture relief painting after hot stamping will have a significant

improvement in both tactile and visual effects on the hot stamping area, presenting a strong metallic luster

and bright and eye-catching colors in the graphics and text. This technique is widely used in various fields such as decorative paintings, packaging, book covers, etc., which can increase the decorative and grade of products. Multi layer printing layering technology for one-time molding of multiple texture schemes The combination of white ink texture, UV full-color, matte oil, and hot stamping oil can achieve a 3D texture relief cultural and artistic product hot stamping effect, all of which can be printed and formed in one go through



K LC LM LK

3W+CMYK+Lc+Lm+Lk+V1+V2 3D Printing texture hot stamping process

Configuration parameter











- -1.8m UV white ink texture relief, matte oil, hot gold oil, 8 colors configuration tape printer;
- -Reasonable head layout and more integrated printing solutions enable users to truly experience brand/quality products;
- -Multiple printing solutions have been completed on one machine, solving the limitation of using one machine and one solution for customers, and achieving customized mass production:



Static electricity removal device Effectively eliminate flying ink and

Intelligent moisturizing ink stack, efficient sealing, long-lasting moisturizing



Heating unit for head base plate Effectively monitor the temperature status of the head and quickly raise the temperature



Negative pressure ink supply system Resolve the issue of ink shortage during printing



Using UV printing technology, UV ink is sprayed onto the substrate through a head, and then the ink is instantly cured using ultraviolet light. During the printing process, uneven relief effects can be created by controlling the thickness of specific white ink. Colorful ink is overlaid on top of white ink, presenting a rich color and threedimensional image.



· Suitable for multiple materials

· Personalized customization



High strength tape guide+ front and rear pressure rod High strength conduction band, no deviation or deformation, long service life;



THK high-precision silent dual rail Effectively reduce work environment noise, improve the printing accuracy and smoothness of the car





The 3D texture relief solution is widely used in multiple fields, including but not limited to exhibition halls, advertising cultural background walls, decorative paintings, art replication, etc.Exhibition Hall,Advertising production,Decoration production,Artwork replication.

OR-5806E UV		TECHNICAL PARAMETER
Model		OR-5806E UV
Print head		Epsoni3200-U1x5+Epsoni3200(8)HDx1
Colour		3W+CMYK+Lc+Lm+Lk+V1+V2
Printing speed	Ordinary eclosion	5 sqm/h
Print mode		Piezoelectric inkjet printing
	Width	1820 mm
Medium	Thickness	1–35 mm
	Weight	60 kg
Print width		1800 mm
Ink box	Туре	UV ink
	Capacity	Continuous supply system (1.5L ink tank)
Curing unit		UV cured water-cooled UV LED lamp
Accuracy		2400 dpi
Voltage		AC 220V ± 10%, 50/60 HZ, 5000W
RIP		Rinprint UV
Machine size / weight		3550 (L) x 1560 (W) x1580 (H) mm / 850 kg
Packaging size / weight		3860 (L) x 1140 (W) x 1800 (H) mm / 920 kg
Environment	Power on mode	Temperature: 15° C – 32° C / humidity: 35 – 80% (No condensation)
	Close mode	Temperature: 5° C – 40° C / humidity: 20 – 80% (No condensation)
Accessories		Data cable, user manual, waste ink cartridges, ink cartridges, RIP software, etc



