

OR-A3 UV (EpsonI3200 (8) -U1HD)

A3高落差多功能UV平板打印机 UV Flatbed Printer

A3高落差
Visual position




(圆柱体、立体产品、纸张/片材等)
(Crystal label, nameplate, sand gold medal and various personalized gifts, etc.)



OR-A3UV配置一颗I3200U1HD喷头,8条墨水通道,使颜色配置更加灵活、同色墨水使用相邻4通道,墨滴落点精度更准确。

OR-A3UV is equipped with an I3200U1HD head and 8 ink channels, making color configuration more flexible.

The same color ink uses adjacent 4 channels, resulting in more accurate droplet landing accuracy.



采用灰度级喷头,支持4级灰度打印,打印出更高精度和更高质量的细腻画质。细腻还原每一处画面细节,让图像层次更分明,亮度、清晰度全面提升,彩印、白色、光油一次成型,工艺简单,大大提升产品的附件价值!

Adopting a grayscale head, supporting 4-level grayscale printing, printing with higher precision and higher quality delicate image quality. Exquisite restoration of every detail in the image, making the image hierarchy more distinct, and comprehensively improving brightness and clarity. Color printing, white, and glossy oil are formed in one go with simple craftsmanship, greatly enhancing the accessory value of the product!

OR-A3 UV (EpsonI3200-U1HD) 打印速度/Printing speed:


W+CMYK+V	4pass-720x1200dpi	0.7-2.4 m ² /h
W+CMYK	6pass-720x1800dpi	0.48-1.5 m ² /h
	8pass-720x2400dpi	0.45-1.2 m ² /h

- 配置汉森主板锐印软件,操作简单灵活,界面操作易懂;
Configure Hoson Riprint software, simple and flexible operation, easy to understand interface operation;
- 印刷尺寸为300毫米(X) x 400毫米(Y);
The printing size is 300 mm (X) x 400 mm (Y);
- 可打印介质厚度1-200 mm;
Optional medium thickness at 1-200 mm;
- 可打印平面材料及多产品直接打印方案;
Printable flat materials and direct printing solutions for multiple products;
- 可视化触摸屏界面,打印操作更便捷;
Visual touch screen interface, making printing operations more convenient;
- 可打印圆柱形材料(可选组件)。
Printable cylindrical materials (optional components).


配置参数 Technical Characteristics



高品质静音拖链,反复运动,保护墨路
Silent drag chain, repeated movement, protecting the ink path



大功率吸风平台材料均匀吸附
High-power suction platform, uniform material adsorption




风冷UV灯固化装置
Air cooled UV lamp curing device



自动保湿清洗组件,保证清洗的稳定性
Automatic moisturizing cleaning component ensures stability during cleaning



500mL墨瓶稳定供墨持续输出
500mL ink bottle with stable ink supply and continuous output




Y轴高品质静音双导轨
Y-axis high-quality silent dual guide rail



喷头底板加热单元
Spray heads bottom plate heating unit



全触摸屏 美观实用 操作便捷
Full touch screen, beautiful and practical, easy to operate



自动材料测高装置
Automatic material height measuring device



标牌标识 Sign identification



工艺饰品 Craft jewelry



圆柱体器皿 Cylindrical vessel



金属制品 metal products



奖牌 medal



包装礼盒 gift box



手机壳定制 Custom Phone Case



沙金奖牌 Sand Gold Medal

适用于各大领域：任何平面及圆柱形材质都可以打印，真正做到无所不印，承印物包括但不限于玻璃、瓷砖、金属、亚克力、木板、T恤、皮革、PVC等
Applications: pen sets, industrial and packaging applications, logos, display props, personalized photos, photo frame production, crystal image products, handmade gifts, souvenirs, lighters, coasters, mobile phone case personalized products, USB flash drives, keychains, ashtrays, broochs, lunch boxes, belts, wallets, wallets, insoles, personalized customized sneakers and printing of high drop processing cylindrical products less than 18cm, etc.

规格参数 SPECIFICATIONS

型号 / Model	OR-A3 UV
喷头配置 / Print Head	1 x Epson i3200 (8)–U1HD
打印精度 / Printing accuracy	Max 720 x 2400dpi
打印规格 / Printing specifications	300 x 400 MM
打印高度 / Printing height	Max 200mm
打印速度 / Print speed	0.4–2.4 m ² /h
介质种类 / Type of medium	玻璃,亚克力,陶瓷,金属,纸,木板,皮革,PVC,PP,PE,PTFE等 Glass, acrylic, ceramic, metal, paper, wood, leather, PVC, PP, PE, PTFE, etc ..
墨水类型 / Ink	UV墨水
墨水颜色 / Ink color	W+CMYK / W+CMYK+V 彩+白/彩+白+光油(可选)
高度调节 / Height adjustment	智能升降平台 Intelligent lifting platform
清洗系统 / Cleaning system	软件自动供墨 / 自动清洗+闪喷 Software automatic ink supply/automatic cleaning+flash spray
供墨系统 / Ink supply system	500ML+自动虹吸+白墨循环搅拌 500ML+automatic siphon+white ink circulation stirring
冷却方式 / cooling method	循环风冷 Circulating air cooling
Rip软件 / Rip software	锐印UV版 / 蒙泰(标配) / PhotoPrint(选配) RiPrint UV / MainTop / PhotoPrint (optional)
数据传输 / Interface	高速千兆网口 Gigabit Ethernet port
环境 / Environment	温度 Temperature:15℃–32℃;湿度 Humidity:35%–80%
电源 / Power supply	AC 110/220V, 50 Hz/60 Hz,450W
图片格式 / Image format	TIFF, JPEG, EPS, PDF,.....
设备尺寸 / 重量 Machine size/weight	1000x750x720mm / 100kg
包装尺寸 / 重量 Packaging size/weight	1200x800x950mm / 140kg

南京欧瑞卡数码科技有限公司 Nanjing ORIC Digital Technology Co., Ltd.

地址：江苏省南京市高淳经济开发区秀山路79号

Add: No.79 Xiushan Road, Gaochun Economic Development Zone, Nanjing City, Jiangsu

网站Web：www.oric-systems.com / www.oric-systems.cn

